

BCD-2000

Mini Customer Display



Spec Sheet

Display

Display Method

STN LCD

Display Color

Blue/White

Active Area

96 x 19.2 mm

Visual Area

99 x 24 mm

Brightness

100 cd/m²

Character Number

20 Characters x 2 Lines

Character Type (Set)

95 Alphanumeric, 6 International

Character Font

8 x 16 dot

Character Size

4.8 x 9.6 mm

Character Space

0.05 mm

Receive Buffer

1K

Emulation

ESC/POS, CD5220, UTC Enhance,
UTC Standard, PD6000

Electrical & Interface

Electrical – Voltage

USB: 5VDC ± 5% (USB Bus Power)

RS232: 5VDC ± 5%

Electrical – Current

500mA

Interface

RS232(for SRP-Q300 only)/USB

Software

Driver

Windows Driver®, OPOS Driver

Developer Tools

Windows SDK, Android™ SDK, iOS® SDK

Exterior

Body Color

Ivory/Black

Rotation Angle

Vertical: 35°

Overall Dimension

130 x 110.3 x 68.5 mm

Product weight

250 g

Environment & Reliability

Operating Temperature

0 ~ 40°C/32 ~ 104°F

Operating Humidity

10 ~ 80 %

Storage Temperature

-20 ~ 55°C/-4 ~ 131°F

Storage Humidity

10 ~ 90 %

Reliability (Display)

50,000 hours (Backlight)