



Item: 1 of 2
Items in order: 0

BIXOLON
Espresso

Extra Shot

Time: 11:25 AM
Reg 1

>CAFE<

BIXOLON Certified
Linerless Media

- The following media is compatible with BIXOLON Printers
- Using non-compatible media may cause technical issues which are not covered by warranty or service agreements



StickyPOS

Media Type	Removable												
Product Line	BT		ECO BT		2CR-11		ECO 2CR-11	40M R	ECO BT	PBE 2HT	FCE 2HT		
PID	BT 58X350	BT 80X350	ECO BT 58X315	ECO BT 80X315	2CR-11 58X350	2CR-11 80X350	ECO 2CR-11 80X315	40MM R L90-9000	ECO BT 40X315	PBE 2HT 40X250	FEC 2HT 58X250	FCE 2HT 80X250	
Dimensions of the Product	Width (mm)	58	80	58	80	58	80	80	40	40	40	58	80
	Roll Diameter (inch)	4		4		4		4	4	4	4	4	4
	Length (feet)	150	350	315	315	350	350	315	350	315	250	250	250
Number of Rolls in Carton	18 or 27	18 or 30	18 or 27	18 or 30	18 or 27	18 or 30	18 or 30	18 or 36	18 or 36	18 or 36	18 or 27	18 or 30	
Paper Weight (gsm)	55	55	55	55	55	55	55	55	55	74	74	74	
Recommended Speed	150 mm/s		100 mm/s		150 mm/s		130 mm/s	150 mm/s	100 mm/s	130 mm/s			
Supporting High Temp	N/A		N/A		N/A			N/A		Supporting			
Applicable Models	SRP-S300T/L, SRP-S200	SRP-S300T/L	SRP-S300T/L, SRP-S200	SRP-S300T/L	SRP-S300T/L, SRP-S200	SRP-S300T/L		SRP-S300T/L, SRP-S200		SRP-S300T/L, SRP-S200		SRP-S300T/L	

Blumberg

Permanent Adhesive				
Linerless Externe				
A11649	A12978	A10944	A14373	A12932
58	80	58	80	112
4	4	4	4	2.2
260	262	328	328	78
-	5	18	18	30
88.0 +/- 8.0	80	93 +/- 10	93 +/- 10	77
100 mm/s	100 mm/s	100 mm/s	100 mm/s	60 mm/s
N/A		N/A		N/A
SRP-S300TX/LX, SRP-S320				SPP-R410

Dykam

Media Type	Permanent Adhesive	
Product Line	Linerless Externe	
PID	4030115	
Dimensions of the Product	Width (mm)	100
	Roll Diameter (inch)	4.9 +/- 0.05
	Length (feet)	394
Number of Rolls in Carton	4	
Paper Weight (gsm)	72 +/- 10	
Recommended Speed	127 mm/s	
Applicable Models	XL5-40	

BIZERBA

Media Type	Full Adhesive		
Product Line	Linerless Top	Eco BK 002C	Linerless Premium Top
PID	402 00000 00209	402 00000 00206	402 00000 00085
Dimensions of the Product	Width (mm)	58	58
	Roll Diameter (inch)	4	4
	Length (feet)	262	262
Number of Rolls in Carton	30	30	30
Paper Weight (gsm)	73	71	80
Recommended Speed	150 mm/s		
Applicable Models	SRP-S300TX/LX, SRP-S320		

NAStar

Media Type	Full Adhesive	
Product Line	NAStar Print'N Stick Eco	NAStar Print'N Stick Plus
PID	SWDXTM1 3.125.155	SWDXTS 3.125.155
Dimensions of the Product	Width (mm)	79.4
	Roll Diameter (inch)	3
	Length (feet)	155
Number of Rolls in Carton	48	48
Paper Weight (gsm)	73	75
Recommended Speed	100 mm/s	130 mm/s
Applicable Models	SRP-S300T/L	

Sato

Media Type	Peelable Adhesive	Permanent Adhesive	
Product Line	Re-stick	Linerless Externe	
PID	585006411	585006451	Y58129231338
Dimensions of the Product	Width (mm)	79.5	80
	Roll Diameter (inch)	4	4
	Length (feet)	240	354
Number of Rolls in Carton	100	100	12
Paper Weight (gsm)	90.8 +/- 10.1	89.7 +/- 8.1	80.0 +/- 10.0
Recommended Speed	170 mm/s	100 mm/s	150 mm/s
Applicable Models	SRP-S300T/L	SRP-S300TX/LX, SRP-S320	

UPM Raflatrac

Media Type	Removable	
Product Line	THERMAL LINERLESS TPFREE CO2N-FSC/ RL50 OPTICUT	
PID	FWK/RL50/00/E0	
Dimensions of the Product	Width (mm)	80
	Roll Diameter (inch)	4
	Length (feet)	260
Number of Rolls in Carton	18	
Paper Weight (gsm)	75	
Recommended Speed	100 mm/s	
Applicable Models	SRP-S300T/L	



ICONEX

Media Type	Classic						Classic High Tack			Classic High Temp			Ultralite			Classic High Tack Plus		Snag Resistant		Freshness Labeling			High-Temp Hi-Tack				
Product Line	9023-1253	9023-1232	9023-1823	9023-1397	9023-1233	9023-1818	9023-1254	9023-1500	9023-1258	9023-1267	9023-1463	9023-1269	9023-1866	9023-1410	9023-1865	9023-1846		9023-1873	9023-1708	9016-3227	9016-3777	9016-3257	9023-2083				
Dimensions of the Product	Width (mm)		80		58		40		80		40		80		58		40		80		40		40		58		
	Roll Diameter (inch)		4						4			4			4			4		4		4			4		
	Length (feet)		270						270			270			375			270		270		225			270		
Number of Rolls in Carton		12	30	12	30	12	30	12		12	30	12	30		12		12		12	30	12		12		12		
Paper Weight (gsm)		80						80			80			55			80		80		80			80			
Recommended Speed		170 mm/s												100 mm/s												150 mm/s	
Supporting High Temp		60°F ~ 120°F (15.5°C ~ 48.9°C)						60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)		60°F ~ 120°F (15.5°C ~ 48.9°C)		0°F ~ 212°F (-17.8°C ~ 100°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)			
Applicable Models		SRP-S300T/L		SRP-S300T/L, SRP-S200				SRP-S300T/L	SRP-S300T/L, SRP-S200		SRP-S300T/L		SRP-S300T/L, SRP-S200		SRP-S300T/L	SRP-S300T/L, SRP-S200		SRP-S300T/L		SRP-S300T/L, SRP-S200		SRP-S300TX/LX, SRP-S320			SRP-S300T/L, SRP-S200		

Media Type	Center Adhesive				Side-Edge Adhesive								Three and Four Stripe Adhesive		Diamond Adhesive Formation				Full Adhesive		Full Adhesive														
						*Available Colors : Blue, Green, Canary, Pink, Orange and Violet																													
Product Line	Premium		2GO		Premium		2GO		Colors		Spectrum		2GO		PLUSD				X2		X2														
Dimensions of the Product	MS 214150	MS 318150	MS 2141602GO	MS 3181602GO	MS 214150SE	MS 318150SE	MS 173223752GO2SHR	MS 214782GOSE	MS 3181602GOSE	MS 3181602GOSE (B,G,C,P,O,V*)	MS 3181602GOSESP	MS 2142402GO3S	MS 3182402GO4S	MS 1732290PLUSD HVHR	MS 214290PLUSD	MS 318170PLUSD	MS 3183752GOPLUSD	MS 11732270X2HRHT	MS 214290X2	MS214125X2	MS318125X2														
	Width (mm)		57		80		57		80		57		80		40		57		80		40		58		58		80								
	Roll Diameter (inch)		3		2.8		3		3		4		2		2.8		2.8		2.8		3.2		3.2		4		4		4		4		2.6		2.6
Length (feet)		150	150	160	160	150	150	375	78	160	160	240	240	290	290	170	375	300	290	125	125														
Number of Rolls in Carton		24	24	24	24	24	24	12	72	24	24	28	32	32	12	32	32	12	12	50	50														
Paper Weight (gsm)		80	80	55	55	80	80	64	55	55	55	55	55	64	80	80	55	64	80	74	74														
Recommended Speed		150 mm/s				150 mm/s		100 mm/s		150 mm/s				150 mm/s		100 mm/s		150 mm/s		100 mm/s		170 mm/s		127 mm/s		127 mm/s									
Applicable Models		SRP-S300T/L				SRP-S300T/L, SRP-S200	SRP-S300T/L	SRP-S300T/L, SRP-S200		SRP-S300T/L				SRP-S300T/L, SRP-S200	SRP-S300T/L		SRP-S300T/L, SRP-S200		SRP-S300T/L, SRP-S200		SRP-S300T/L, SRP-S200	SRP-S300T/L													

BIXOLON Certified Linerless Media



BR_BIXOLON Certified Linerless Media_EN_OCT24_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON

www.BIXOLON.com

BIXOLON Co.,Ltd.
+82 31 218 5500
sales@bixonon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixononusa.com

BIXOLON Mexico
+521 55 8852 7880
marcelo@bixononusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixonon.de

BIXOLON MEA
+971 4 222 6480
russell@bixonon.com